

SDS Number: LIM025 Revision Date: 1/1/17

Page 1 of 6

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC 750 LAKE COOK ROAD SUITE 440 BUFFALO GROVE, IL 60089

Emergency: Emergency Phone: (800) 424-9300 (ChemTrec

Contact: ChemTrec Acct #: CCN792719

Phone: (847) 215-1144 **Fax:** (847) 215-0577

Product Name: Seed Aide®
Revision Date: 1/1/17
SDS Number: LIM025
CAS Number: Not applicable

Product Use: Erosion control and revegetation mulch for hydraulic seeding

Product Description: Pellets of green dyed cellulose fibers from shredded waste paper sources.

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

No GHS Classifications Indicated

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: NONE

no GHS pictograms indicated for this product

GHS Hazard Statements:

no GHS hazards statements indicated

GHS Precautionary Statements:

no GHS precautionary statements indicated

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Inhalation, skin contact, eye contact

Inhalation: Cellulose dust may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate

pre-existing respiratory conditions.

Skin Contact: Cellulose dust can cause irritation. Skin absorption is not known to occur.

Eye Contact: Cellulose dust can irritate the eyes. **Ingestion:** No reports of human ingestion.

OSHA Classification: Cellulose dust is a hazardous substance as defined by the Hazard Communication Standard

29CFR 1910.1200



SDS Number: LIM025 Revision Date: 1/1/17

Page 2 of 6

NFPA: Health = 1, Fire = 1, Reactivity = 0, Specific Hazard = n/a



COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas# % Chemical Name

0 Proprietary Hydrocolloidal Based Polysaccharide Tackifier

9000300 Proprietary Guar Gum

FIRST AID MEASURES

Inhalation: Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation

persists.

Skin Contact: Usually not a problem. Wash off with running water if irritation is experienced.

Eye Contact: Open eyelids and flush with water.

Ingestion: Get medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: Combustible product
Flash Point Method: Not applicable

Not applicable

Autoignition Temp: 200-260°C (400-500°F) Conditions to avoid: In contact with flames or hot surfaces Flammable- Extinguish with water; same as a wood fire

ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

HANDLING AND STORAGE

Handling Precautions: Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne

dust concentrations.

Storage Requirements: Store in a cool, dry place. Keep away from sources of ignition.





SDS Number: LIM025 Revision Date: 1/1/17

Page 3 of 6

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling

operations.

Personal Protective Equipment:

Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of

dust entering the eyes.

Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.

Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with

dust cartridges will generally provide adequate protection.

Footwear: The product is slippery when wet. Wear appropriate footwear.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dyed, green pellets - Shredded waste paper

Physical State: Cellulose Fibers Odor: Mild wood odor

Spec Grav./Density:Lighter than waterSolubility:N/ABoiling Point:N/AFreezing/Melting Pt.:N/AVapor Pressure:N/AVapor Density:N/A

pH: N/A

10 STABILITY AND REACTIVITY

Chemical Stability: Stable product

Conditions to Avoid: Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in

excess of 200°C (400°F).

Materials to Avoid: Strong acids and oxidizers

Hazardous Decomposition: None Determined **Hazardous Polymerization:** Will not occur.

11 TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer. Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Particulates Not Otherwise

Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust);

5 mg/m³ (Respirable fraction)

Irritancy: Cellulose could be a mild irritant.

Sensitization: Some cellulose dusts may cause allergic skin reactions.



SDS Number: LIM025 Revision Date: 1/1/17

Page 4 of 6

49

ECOLOGICAL INFORMATION

Guar Gum (CAS# 9000-30-0) is listed as an inert ingredient permitted for use in nonfood use pesticide products by EPA. It is also classified under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA) as a minimal risk inert substance (List 4A) meaning that as a pesticide, Guar Gum is considered by the EPA to pose little or no risk to humans or the environment. The Us Department of Agriculture (USDA) National Organic Program (NOP) also allows the use of Guar Gum in a variety of applications, but primarily as a pesticide in organic production operations. Finally, Guar Gum is listed on the Generally Recognized as Safe (GRAS) list by the Food and Drug Administration (FDA).

48-hr LC₅₀ = >100% for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

12

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

1/

TRANSPORT INFORMATION



SDS Number: LIM025 Revision Date: 1/1/17

Page 5 of 6

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Hydrocolloidal Based Polysaccharide Tackifier (0) [Proprietary]

Guar Gum (9000300) [Proprietary] TSCA

Regulatory CODE Descriptions

TSCA = Toxic Substances Control Act

COMPONENT / (CAS/PERC) / CODES

*Guar Gum / (9000300 n/a%) / TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List

NRC = Nationally Recognized Carcinogens

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

EHS302 = Extremely Hazardous Substance

EPCRAWPC = EPCRA Water Priority Chemicals

HAP = Hazardous Air Pollutants

NJEHS = NJ Extraordinarily Hazardous Substances

NJHS = NJ Right-to-Know Hazardous Substances

OSHAPSM = OSHA Chemicals Requiring process safety management

SARA313 = SARA 313 Title III Toxic Chemicals







SDS Number: LIM025 Revision Date: 1/1/17

Page 6 of 6

16

OTHER INFORMATION

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).